



Description: 0.283" Right Angle / Machined

Dimensions (inch/mm)						
Pins	A	B	C	D	E	F
9	1.213	0.984	0.665	0.327	0.240	0.492
	30.80	25.00	16.90	8.30	6.10	12.50
15	1.543	1.311	0.994	0.327	0.240	0.492
	39.20	33.30	25.25	8.30	6.10	12.50
25	2.089	1.852	1.533	0.327	0.240	0.492
	53.05	47.05	38.95	8.30	6.10	12.50
37	2.732	2.500	2.181	0.327	0.240	0.492
	69.40	63.50	55.40	8.30	6.10	12.50
50	2.638	2.402	2.079	0.429	0.236	0.602
	67.00	61.00	52.80	10.90	6.00	15.30



Material:

Shell: Nickel Plated Steel
Insulator: Glass-Filled Nylon Thermoplastic, UL94 V-0
Process Temperature: 260°C
Contact: Precision Machined Copper Alloy

Electrical:

Current Rating: 5 AMPS
Contact Resistance: 10 mOhms Max.
Insulation Resistance: 5 GOhms Min.
Dielectric Withstanding Voltage: 1000 VAC for 1 minute
Working Voltage: 250V
Temperature: -55° C TO +125° C

1 7 3 - E Y Y - 1 1 Y R Y Y 1

Series
Position
E09
E15
E25
E37
E50
Gender
1 = Male
Termination
1 = PCB Mounting
Shell Plating
3 = Nickel
RoHS Compliant
Hardware Options
00 = No Hardware
0A = 0.098" Clinch Nut (Board Side)
14 = Standard Bracket with 4-40 Screwlock
24 = Standard Bracket with 4-40 Captive Screw
46 = Boardlock Bracket with 4-40 Insert
Plating Options
1 = Gold Flash
2 = 30μ" Gold
3 = 50μ" Gold

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
PAM JENKINS

DATE:
11/28/2005

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING

NorComp






SCALE:
NTS

SHEET OF
1 3

REV
25

DWG NO.

173-EYY-11YRY1



UNITS = inch

* Typical Suggested Size
May Not Be Suitable For All Applications

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
PAM JENKINS

DATE:
11/28/2005

NorComp

SCALE:
NTS


SHEET
2 OF
3

REV
25

DWG NO.
173-EYY-11YRYY1


0A Hardware Option

0.098" Clinch Nut (Board Side)




Clinch Nut has 4-40 Internal Threads

14 Hardware Option		
	Description	NorComp Part Number
1	4-40 Screwlock	SFSO4401NR
2	Bracket	K501CZ
3	Lock Washer	LW1-T
4	4-40 Nut	N4401N



**Search Hardware Part Number To Obtain Technical Specifications.

24 Hardware Option		
	Description	NorComp Part Number
1	4-40 Captive Screw	SSH4401T
2	Bracket	K501CZ
3	Lock Washer	LW1-T
4	4-40 Nut	N4401N




**Search Hardware Part Number To Obtain Technical Specifications.


46 Hardware Option

Boardlock Bracket and 4-40 Insert


#4-40 Threaded Insert



9-37 Position Connector Boardlock Bracket



50 Position Connector Boardlock Bracket
** 50 Position Comes With Locator Plate



Boardlock Brackets Come Assembled On Connector

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
PAM JENKINS
DATE:
11/28/2005

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING

NorComp

SCALE: NTS	SHEET 3 OF 3	REV 25
DWG NO. 173-EYY-11YRY1		